


P/N: TT 1U 24 SCD LCQ



RECEIVES UP TO 2 SPLICE TRAYS 24
FO P/N: 48K724F02298



INTEGRATED ROUTING MANAGEMENT



LATERAL PATCHING
MANAGEMENT RINGS



19" TELESCOPIC RAILS

APPLICATIONS

Ideal for various applications such as vertical or horizontal cabling for distribution, the 19" TT1Ux patch panel facilitates access and maintenance for indoor applications. It offers a real save of time for the technician, and is based on 4 different capacities. It is a truly secured transition point for connecting ST, FC, SC or LC in singlemode or multimode applications.

GENERAL CHARACTERISTICS

- 24 ST, SC OR FC SIMPLEX OR DUPLEX 24 LC DUPLEX OR QUAD
- THE FRONT PANELS CAN BE EASILY REMOVED
- 96 FIBERS WITH 24 LC QUAD ADAPTERS
- ONE NUMBERED LABEL INSIDE THE DOOR



MECHANICAL PROPERTIES

MATERIAL	HIGH RESISTANCE ABS IDEAL AGAINST CORROSION
RAL	RAL 7016 DARK GREY
INPUTS	2 REAR CABLE ENTRIES FOR PG13.5 CABLE GLANDS
SYSTEM	LOCKING THANKS TO 2 BLACK BUTTONS
DIMENSIONS	WIDTH 482.6 MM (19") X DEPTH 300 MM X HEIGHT 44 MM DEPTH WHEN THE PANEL IS OPENED: 500 MM WIDTH OF THE TELESCOPIC SLIDE PANEL: 435 MM
WEIGHT	2.2 KG
PACKAGING	UNIT

STANDARDS

ENVIRONMENTAL PROTECTION ACCORDING TO:	2002/95/EC (ROHS), SVHC (SUBSTANCE VERY HIGH CONCERN)
--	---

ORDER INFORMATION

ITEM NO	DESCRIPTION	PACKAGING	NVG#
TT 1U 24 SCD LCQ	TELESCOPIC SLIDE 1U PANEL FOR 24 HORIZONTAL STD, FCD, SCD OR LCQ	UNIT	2010070
48K724F02298	SPLICE TRAY 24F	UNIT	2010071